



ProODO™

Handheld Optical Dissolved Oxygen Meter

The new ProODO™ provides traditional YSI quality in a handheld dissolved oxygen instrument with luminescent optical dissolved oxygen (DO) technology. The ProODO utilizes “smart” digital sensor technology which stores calibration data within the sensor. This allows probes to be placed on any ProODO instrument without re-calibration.



The ProODO is a digital signal instrument. Any ProODO cable can be connected and used on any ProODO instrument. The luminescent optical probes hold the calibration information internally.

Optical DO™

YSI ODO technology reduces the time required calibrating and maintaining sensors while utilizing a user replaceable sensing element that requires approximately an annual replacement. There are no electrodes to clean or solutions to change. Based on usage, calibrations can be stable for up to one year and are stored in each sensor.

Optical technology also increases DO accuracy and eliminates probe fouling by common gases such as hydrogen sulfide.

- Expanded DO range of 0-500% with a response time of T90 in 15 seconds
- Non-consumptive luminescent method eliminates stirring
- Easy to read graphic, backlit display and keypad for use in any lighting condition
- Truly field-worthy, impact resistant, IP-67 waterproof case and connectors; rubber over molded, non-slip case, for extra durability and grip
- User-replaceable cables in lengths of 1 to 100-meters; cable management kit included with 4-meter and longer cables
- USB connection allows interaction with powerful desktop Data Manager software
- Stores 2000 data sets (sensor data, date, time, site and user defined information)
- Multiple languages include English, Spanish, French, Italian, Norwegian, Portuguese and German. Asian language support in the future.
- 3-year instrument warranty; 2-year cable and probe warranty

Pure
Data for a
Healthy
Planet.®



+1 937 767 7241
800 897 4151 (US)
www.yssi.com

YSI Environmental
+1 937 767 7241
Fax +1 937 767 9353
environmental@yssi.com

YSI Integrated Systems
+1 508 748 0366
systems@yssi.com

SonTek/YSI
+1 858 546 8327
inquiry@sontek.com

YSI Gulf Coast
+1 225 753 2650
environmental@yssi.com

AMJ Environmental
+1 727 565 2201
amj@yssi.com

YSI Hydrodata (UK)
+44 1462 673 581
europe@yssi.com

YSI Middle East (Bahrain)
+973 1753 6222
halsalem@yssi.com

YSI (Hong Kong) Limited
+852 2891 8154
hongkong@yssi.com

YSI (China) Limited
+86 532 575 3636
beijing@yssi-china.com

YSI Nanotech (Japan)
+81 44 222 0009
nanotech@yssi.com

YSI India
+91 989 122 0639
sham@yssi.com

YSI Australia
+61 7 390 17223
acorbett@yssi.com

ISO 9001
ISO 14001

ProODO and ODO are trademarks and Pure Data for a Healthy Planet and Who's Minding the Planet? are registered trademarks of YSI Incorporated.

©2008 YSI Incorporated
Printed in the USA 1008 W3



YSI incorporated
Who's Minding
the Planet?™

ProODO System Specifications (instrument with cable and probe)

Dissolved Oxygen (% saturation)	Sensor Type	Optical (dynamic luminescence quenching lifetime detection)
	Range	0 to 500% air saturation
	Accuracy	0 to 200% air saturation, ± 1% of the reading or ± 1% air saturation, whichever is greater; 200 to 500% air saturation, ± 15% of the reading
Dissolved Oxygen (mg/L)	Resolution	0.1% air saturation
	Sensor Type	Optical (dynamic luminescence quenching lifetime detection)
	Range	0 to 50 mg/L
Temperature (°C, °F, °K)	Accuracy	0 to 20 mg/L, ± 0.1 mg/L or ± 1% of reading, whichever is greater;
	Resolution	20 to 50 mg/L, ± 15% of the reading
	Resolution	0.01 or 0.1 mg/L (auto-scaling)
Barometer (mmHg, inHg, mBar, Psi, KPa)	Range	-5 to 70°C
	Accuracy	± 0.2°C
	Resolution	0.01°C
Barometer (mmHg, inHg, mBar, Psi, KPa)	Range	375 to 825 mmHg
	Accuracy	± 1.5 mmHg from 0 to 50°C
	Resolution	0.1 mmHg

ProODO Additional Specifications

Storage Temperature	-20 to 70°C
Size	8.3 cm width x 21.6 cm length x 2.3 cm depth (3.25 in x 8.5 in x 2.25 in)
Weight with batteries	475 grams (1.05 lbs)
Probe Dimensions	19 cm length (7.5 in); 2.4 cm diameter (0.95 in)
Power	2 alkaline C-cells
Cable Lengths*	1- 4- 10- 20- 30- 40- 50- 60- and 100-m; (3.3, 13.1, 32.8, 65.6, 98, 131, 164, 197 and 328 ft)
Connectors	MS (military spec) waterproof with bayonet lock
Warranty	3-year instrument; 2-year cable and probe; 1-year sensor cap
Salinity Input Range	0-70 ppt; manual (automatically compensates for manual input value)
Data Memory	2000 data sets (sensor data, date, time, site and user defined information)
Flow Dependence	None
Response Time	90% of reading within 15 seconds
Calibration	DO - one point or two point with a zero % value; barometer - one point
Languages	English, Spanish, German, French, Italian, Norwegian, Portuguese; Asian language support in the future
Certifications	RoHS, CE, WEEE, C-Tick, VCCI, IP-67, 1-meter drop test, Assembled in USA
Connectivity	USB 2.0; communications saddle and USB cable included
Data Management	Data Manager desktop software included; 100 user defined folders and site names
User ID	Optional User ID for data security
Measurement/Logging Modes	Automatic and Manual sampling modes/Continuous and Interval logging modes
GLP Compliant	Yes
Probe/Sensor Materials	The following materials may come into contact with the sampling environment: Xenoy® PBT Polycarbonate blend, Noryl, Stainless Steel, Titanium, Polyurethane, Santoprene, Acrylic, Polystyrene

ProODO Ordering Information (order items separately)

626281	ProODO Handheld instrument
626320	Replacement sensing element (included with initial probe purchase)
626250-1	1-m probe/cable for DO/temp
626250-4	4-m probe/cable for DO/temp (includes cable management kit)
626250-10	10-m probe/cable for DO/temp (includes cable management kit)
626250-20	20-m probe/cable for DO/temp (includes cable management kit)
626250-30	30-m probe/cable for DO/temp (includes cable management kit)
626250-40	40-m probe/cable for DO/temp (includes cable management kit)
626250-50	50-m probe/cable for DO/temp (includes cable management kit)
626250-60	60-m probe/cable for DO/temp (includes cable management kit)
626250-100	100-m probe/cable for DO/temp (includes cable management kit)

Accessories Ordering Information (visit yssi.com/accessories)

603075	Soft-sided carrying case
603074	Hard-sided carrying case
603069	Belt clip to attach instrument to belt
063517	Ultra clamp (attach to instrument to secure it to a desk, boat, etc)
063507	Small tripod (attach to instrument to sit on any flat surface)
603062	Cable management kit (included with 4- through 100-m cables)
605978	Cable weight, 4.9 oz, attach to stainless steel probe guard

* Special order cable lengths up to 100-meters in 10-meter increments available.



603069 belt clip



603062 cable management kit



603075 soft-sided carrying case with ProODO, cable, and accessories